



## Technical Data Sheet

**Application fields:** Self-adhesive collar for sealing heat-resistant openings through the airtight level, e.g. for vapour barriers, sarking membranes. Heat-resistant up to 250°C.

### Adhesive sleeve

**Material:** HDPE carrier film (Tyvek®) / polyacrylate adhesive glue  
**Colour:** white  
**Thickness:** approx. 0.2 mm Tyvek® carrier film / approx. 0.12 mm adhesive glue  
**Adhesive force:** > 25N/25mm  
**Tensile strength:** > 50N/25mm  
**Temperature resistance:** -30 °C to +100 °C  
**UV resistance:** very good

### Flexible sealing grommet

**Material:** heat-stabilised silicone  
**Colour:** red  
**Hardness:** 60 ± 5 Shore A (DIN 53505)  
**Density:** 1.17 g / cm<sup>3</sup> (DIN EN ISO 1183-1A)  
**Tear strength:** ≥ 8 MPa (DIN 53504-S2)  
**Temperature resistance:** -50 °C to +200 °C (short-term 250 °C)  
**UV resistance:** very good

**Storage:** cool and dry

**Processing temperature:** +5 °C to +40 °C

**Halogen-free:** yes

**Processing notes:** The area must be dry, stable and free of dust and release agent.  
Folds and kinks must be prevented.